PAT-NO: JP406202813A

DOCUMENT-IDENTIFIER: JP 06202813 A

TITLE: METHOD FOR SYNCHRONIZATION OF REDUNDANT DISK DRIVE ARRAY

PUBN-DATE: July 22, 1994

INVENTOR-INFORMATION:
NAME
MENDELSOHN, NOAH

ASSIGNEE-INFORMATION:

NAME	COUNTRY
INTERNATL BUSINESS MACH CORP <IBM>	N/A

APPL-NO: JP05159626

APPL-DATE: June 29, 1993

INT-CL (IPC): G06F003/06, G06F003/06

ABSTRACT:

PURPOSE: To provide a redundant configuration of a disk drive having an
improved data synchronizing method on the occurrence of a service interruption.

CONSTITUTION: The system includes the same plural nodes

which are connected
to each other, and each node includes a disk drive, an NVRAM and a processor.
The system traverses disk drives in different nodes and stores data in a RAID
or a mirrored system. An NVRAM in a parity node is provided with new data, the
copies of old data obtained from the nodes and an entry containing a synchronous state after the data are stored. The parity node decides a new
parity and sends it to a data node. The parity node resets a synchronous
indicator after receiving a notice. When power source is applied after a
service interruption, the parity node scans the NVRAM to decide whether an
entry exists in it and sends new data to an addressed data node when a
non-reset state is detected. Thus the synchronization is secured between the
data and parity nodes.